VH1F

12kV 800...2000A 25kA FIXED VCB AIR INSULATED SWITCHGEAR

Safe Reliable Compact



Compact, modular & minimal maintenance fixed VCB Air Insulated Switchgear

The foundation of TAMCO's Air Insulated Switchgear is built around innovation, technology, intelligence and flexibility combined with highest quality. VH1F is a fixed VCB Switchgear for application upto 12kV 25kA 2000A that satisfies all the latest international standards. VH1F offers the flexibility and reliability of GIS type but with air insulation. It has ample termination space, higher air clearance yet has the most compact dimensions.


VH1F is designed for higher operational safety, minimal maintenance with an impressive small footprint. VH1F's modular design provides a perfect platform for building reliable distribution network in a compact space.

With a worldwide after sales and service network, TAMCO ensures that the experts nearest to customer region are available for customer support at all time.





FRONT





Type-tested according to IEC 62271-100, IEC 6227-200 & IEC 62271-102

Loss of Service Continuity: LSC2B
Partition Class: PM

Internal Arc Classification: IAC AFLR 25kA –1s
Ingress Protection Class: IP4X for cubicle

and the state of t				
Electrical Characteristics		800A	1250A	2000A
Rated Voltage	kV	12		
Rated Current	А	800	1250	2000
Rated Frequency	Hz	50		
Rated Short Time Current	kA/3sec	25		
Rated s.c. Making Current	kAp	63		
Rated s.c. Sym. Breaking Cur.	kA	25		
Rated Impulse Voltage (1.2/50)	kVp	75 / 95		
Rated a.c. 1 min pf Voltage	kV rms	28 / 38		
Width	mm	45	0	700
Depth**	mm	1300 / 1700		
Height**	mm	2300		
·			·	·

DESIGN FOR SAFETY

TAMCO regards safety as the most important specification of switchgear design and operation and the following proven safety features have been built into type VH1F.

- No exposure to live parts
- Operational safety due to incorporation of PERMISSIVE interlock, PROOF OF EARTH, POINT OF ISOLATION etc*.
- Comprehensive pad locking facilities
- Mimic diagrams and position indicators to guide the operators
- Arc fault tested at 25kA for 1 sec

PRODUCT VARIANTS

Circuit breaker incomer and outgoing panel

* Height and Depth may vary on different configurations.

- Bus sectioniser
- Bus Riser
- Metering panels
- Plugin type Line VT / Bus VT
- Surge arrester
- Cable entry from top/ bottom, front/rear

FEATURES

- Most compact foot print with rigid structure
- Reduced substation dimensions saving civil and land costs
- Option for front, rear and dry type cable termination with cable entry from bottom and top
- Safe, positive and fool proof interlocks
- Cable door & VCB interlocked
- Pad-lockable VCB & 3-position isolator duly interlocked
- Fully modular design with extension on both sides
- Fixed VCB with motorised mechanism for switching
- Front cable entry & no rear clearance required
- Position of 3 position switch directly and easily visible without opening any cover in addition to the indicator

CUSTOMER BENEFITS

- Reduces cubicle space requirement and therefore saving in civil and last cost
- Mechanical endurance (M2) 10000 operations
- Safe operation behind close door
- Internal Arc classification AFLR 25kA 1 sec
- Voltage detection system (VDS) as standard offering
- Cost optimised solution for distribution networks
- Peace of mind with very less maintenance
- Option of fixed VT with draw out primary fuses
- Flexibility of accommodating higher numbers CT's
- Ease of operation with direct and self exploratory interlocks/indicators

TAMCO

TAMCO Switchgear (Malaysia) Sdn Bhd

Sub Lot 24, Lot 16505, Jalan Keluli 1, P.O.Box 2100, Kawasan Perindustrian Bukit Raja Seksyen 7, 40802 Shah Alam, Selangor Darul Ehsan, Malaysia.

Tel : +603-3361 8200 Fax : +603-3341 6200 Email : sales@tamco.com.my

Our Sales & Marketing Offices:

- Malaysia
- UAE
- Australia
- Qatar
- Indonesia
- Oman
- KSA
- India

www.tamco.com.my

VH1F-R0

^{*} Optional on customer request.